



Wires, Cables & Cords

# Hook-up Wires

ELECTRIFYING YOUR FUTURE



Deltacab hook-up and lead wire products are manufactured in a variety of materials, sizes and designs to meet rigid industry and government specifications. Deltacab always ensures consistent quality of these products by continuously monitoring the manufacturing process and Copper and PVC compound compositions.

The hook-up and lead wire products can be used in numerous applications including interconnection circuits, internal wiring of computer and data processing equipment, appliances, lighting, motor leads, heating and cooling equipment, harness fabrication and automotive.



The hook-up and lead-wires are available in variety of colours and customization is possible too.

Sr. No.	AWG	Stranding	OD		Insulation Thickness	
			Inch	mm	Inch	mm
1	30	Solid	0.030	0.76	0.010	0.25
2	30	7 x 38	0.032	0.81	0.010	0.25
3	28	Solid	0.033	0.84	0.010	0.25
4	28	7 x 36	0.035	0.89	0.010	0.25
5	26	Solid	0.036	0.91	0.010	0.25
6	26	7 x 34	0.039	0.99	0.010	0.25
7	24	Solid	0.040	1.02	0.010	0.25
8	24	7 x 32	0.044	1.12	0.010	0.25
9	22	Solid	0.047	1.19	0.010	0.25
10	22	7 x 30	0.050	1.27	0.010	0.25
11	20	7 x 28	0.057	1.45	0.010	0.25
12	20	10 x 30	0.056	1.42	0.010	0.25
13	18	16 x 30	0.067	1.70	0.010	0.25
14	18	19 x 30	0.066	1.68	0.010	0.25
15	16	19 x 28	0.078	1.98	0.010	0.25
16	16	26 x 30	0.080	2.03	0.010	0.25

- Available in Annealed Bare Copper (ABC) / Annealed Tinned Copper (ATC) and Semi-rigid PVC Insulation