



Wires, Cables & Cords

Moulded Cords

ELECTRIFYING YOUR FUTURE



Deltacab is into manufacturing of 2 Pin and 3 Pin Moulded Cords since the past 20 years and it has achieved great milestones in the industry. Deltacab masters the art and specializes in designing moulded cords as per the application and customer requirements. Deltacab is the market leader as well as the pioneer in the field when it comes to moulded cord manufacturing in India.

Deltacab has a rich customer base and manufactures moulded cords which adhere to IS:1293 and IEC standards. The moulded cords manufactured are used in various applications such as Flexi-cords, Extension cords, Spike guards, Hand blenders, Mixers, Home appliances, Refrigerators, Vacuum Cleaners, Air conditioners, Juice Mixers, Refrigerators, Testing Equipments, Washing Machines, TVs, Audio Video Systems, Computer Peripherals, Weighing Scales, etc.

Deltacab believes in making high-quality moulded cords which are durable and reasonable at the same time. All types of moulded cords are manufactured including 2 Pin, 3 Pin, Indian Standard, UK plug type (with Fuse), etc.

We cover all aspects of R&D in moulded cords from Engineering Drawing Preparation, Pilot Lots, Testing, to the final mass production. We also give special packaging as per the customer's preference and the application. Moulded cords are also available in all the colours according to the customer's requirement. Length is also customizable. Hence to conclude, Deltacab is the one stop solution for Moulded Cords from designing to huge volume production.



The list of the moulded cord Deltacab manufactures is as follows:

2 PIN MOULDED CORDS								
SR.	No. of Strands / Strand Dia.	Sq. mm	Conductor Dia.	No. of Core	Shape	O.D. (mm)	AMPERES	Standard
			(+/- 0.01mm)					
1	14/0.152 mm	0.25	0.152 mm	2	Flat	3.30 x 5.00 +/- 0.20	1.50	Non IS
2	14/0.152 mm	0.25	0.152 mm	2	Round	5.10 +/- 0.20	1.50	Non IS
3	16/0.20 mm	0.50	0.20 mm	2	Flat	3.60 x 5.60 +/- 0.20	4.00	Non IS
4	16/0.20 mm	0.50	0.20 mm	2	Flat	6.20 x 4.20 +/- 0.20	4.00	IS 1293
5	16/0.20 mm	0.50	0.20 mm	2	Round	6.00 +/- 0.20	4.00	IS 1293
6	24/0.20 mm	0.75	0.20 mm	2	Flat	4.50 x 6.50 +/- 0.20	6.00	IS 1293
7	24/0.20 mm	0.75	0.20 mm	2	Round	6.50 +/- 0.20	6.00	IS 1293

3 PIN MOULDED CORDS

SR.	No. of Strands / Strand Dia.	Sq. mm	Conductor Dia. (+/- 0.01mm)	No. of Core	Shape	O.D. (mm)	AMPERES	Standard
1	14/0.152 mm	0.25	0.152 mm	3	Round	6.00 +/- 0.20	1.50	Non IS
2	16/0.20 mm	0.50	0.20 mm	3	Round	6.50 +/- 0.20	4.00	IS 1293
3	24/0.20 mm	0.75	0.20 mm	3	Round	7.10 +/- 0.20	6.00	IS 1293
4	48/0.20 mm	1.50	0.20 mm	3	Round	8.10 +/- 0.20	16.00	IS 1293